

# How to clean carpet with the Britex Deep Cleaning Machine



Live clean, love Britex.

- 1 Firstly, set up your Britex Machine for carpet cleaning.

Pull back the brass sleeve on the end of the of the black solution hose and attach it to the carpet wand underneath the trigger until it locks into place. Release the sleeve.



- 2 Pull back the smaller brass end of the black solution hose and insert it into the connection under the button at the front of the machine under the vacuum and pump switches.



- 3 Connect one end of the larger vacuum hose to the Tank A dome lid, and the other end to the carpet wand tube just above the wand trigger.



Call our Helpline on 1800 804 973 for assistance.

[www.britex.com](http://www.britex.com)

**4** Remove dome lid from Tank A.

Add 2 capfuls of Britex defoamer. Replace the dome lid securely.



**5** Fill Tank B with 9L of hot water, ensuring the water level does not go above the filter.

Add 3 capfuls of Britex Carpet Cleaning Solution.



**6** Plug the machine into your power point.

Turn both vacuum and pump buttons on.

Place the floor wand face-down onto the carpet.



**7** Use the Britex wand like you would a vacuum, moving the head forwards and backwards over the carpet.

Hold in the spray lever on the wand to apply water and solution to the carpet. To STOP spraying water, release the trigger on the wand. Then move the wand head over the dampened area to remove water and dirt, as if vacuuming your carpet.

**For every pass where you spray water, use 2-3 passes WITHOUT spraying to extract the water and dirt from the carpet.**

Repeat this process over stained areas.

**IMPORTANT:** Apply a light spray of water – do not saturate the carpet.



**Call our Helpline on 1800 804 973 for assistance.**

[www.britex.com](http://www.britex.com)

- 8** If tank B is empty, refill with 3 capfuls of Britex Carpet Cleaning solution and 9 litres of hot tap water.



- 9** Periodically check tank A and discard the dirty water when required. Refill Tank A with 2 capfuls of Britex Defoamer if you are continuing to clean.

## When you are finished cleaning

Release any unused solution from Tank B using the tap at the back of the machine and empty out the dirty water from Tank A. Rinse out the dome lid and filter. Clean the machine thoroughly before returning it to store.

## STILL NEED HELP?

Watch our how-to videos at [Britex.com/support](https://www.britex.com/support)

OR call us 7 days a week on 1800 804 973.

Call our Helpline on 1800 804 973 for assistance.

[www.britex.com](https://www.britex.com)